



1. Electrical Characteristics

- 1.1 Impedance: 50 Ω
- 1.2 Working Frequency: DC-3 GHz
- 1.3 S.W.R.: ≤ 1.5
- 1.4 Working Voltage: 3.35 V
- 1.5 Insulation Resistance: 50000 MΩ
- 1.6 Contact Resistance: center contact: 3 mΩ
- 1.7 External Contact: ≤ 2 mΩ

Model No.: SMA-KE-P902

Material: Brass base, with gold-plated surface  
 SMA-KE straight head (180 degrees) - external screw type, internal pin,  
 half thread – P type offset 4 angles

2. Work Environment

- 2.1 Operating Temperature range: -55 °C ~ + 125 °C
- 2.2 Salt Spray Test: 48 H

3	PIN OD1.40*10.00	Brass with gold-plated surface 3u"	SMA014010G-1858	1
2	Insulator OD4.18*7.20	PTFE White	SMA418072I-1751	1
1	Screw thread SQ9.50*14.28	Gold-plated 1u"	SMA951428G-1460	1
Item No.	Part Name/Specification	Material	Part No.	QTY.

		<b>DreamLNK®</b> 深圳市骏晔科技有限公司 SHENZHEN DREAMLNK TECHNOLOGY CO., LTD			
Tolerance 未注公差		Part Name. 品名	SMA-KE-P901		
.X ±0.2		Material. 材			
.XX ±0.10		Finish. 理			
.XXX ±0.05		Scale. 比例	1:1	Draw .	Check. 核
未注角度公差 ±1°		REV. 版本/次	A/0	19.01.01	App. 核准
		Unite. 位	mm	19.01.01	19.01.01