



Model No.: SMA-KE-P903

Material: brass with gold-plated surface

SMA-KE female straight head (180 degrees) - external screw type, internal hole, 11.5 thread – P type offset 4 feet

1. Electrical Characteristics

1.1 Impedance: 50 Ohm

1.2 Working Frequency: DC-3 GHz

1.3 S.W.R.: ≤1.5

1.4 Working Voltage: 335V/ Max

1.5 Insulation Resistance: 5000 Mohm

1.6 Contact Resistance: Center contact: 3 Mohm

1.7 External contact: ≤2 Mohm

2. Work Environment

2.1 Operating Temperature Range: -55°C ~ +125°C

2.2 Salt Spray Test: 48H

5	Spring Washer OD10.20*1.10	Brass with gold-plated surface		1
4	Nut H8.00*1.75	Brass with gold-plated surface		1
3	PIN OD1.40*15.0	Brass with gold-plated surface	SMA014015G-1861	1
2	Insulator OD4.18*10.70	PTFE White	SMA418107I-1772	1
1	Screw thread SQ6.50*17.0		SMA065017G-0760	1
Item No.	Part Name/Specification	Material	Part No.	QTY.

		<b>DreamLNK</b> ® 深圳市骏晔科技有限公司 SHENZHEN DREAMLNK TECHNOLOGY CO., LTD			
Tolerance 未注公差		Part Name. 品名		SMA-KE-P902	
.X ±0.2		Material. 材			
.XX ±0.10		Finish. 理			
.XXX ±0.05		Scale. 比例	1:1	Draw .	Check. 核
未注角度公差 ±1°		REV. 版本/次	A/0	2019.01.29	App. 核准
		Unite. 位	mm	2019.01.29	2019.01.29